




Flat fan nozzles

Series 616 / 617



Spray angle	Ordering no.			A Ø [mm]	E Ø [mm]	V̇ [l/min]							Spray width B at p = 2 bar		
	Type	Material-no.				p [bar]							 H = 250 mm H = 500 mm		
		16 1.4305/303 SS	17 1.4571/316 SS			30 Brass	0,5	1,0	2,0	[US gal./ min] at 40 psi	3,0	5,0			10,0
120°	616. 727	○	○	○	3,00	1,60	3,15	4,45	6,30	1,95	7,72	9,96	14,09	975	1755
	616. 767	○	○	○	3,50	1,70	4,00	5,66	8,00	2,48	9,80	12,65	17,89	970	1750
	616. 807	○	○	○	4,00	2,00	5,00	7,07	10,00	3,10	12,25	15,81	22,36	965	1740
	616. 887	○	○	○	5,00	2,60	8,00	11,31	16,00	4,96	19,60	25,30	35,78	955	1730
	616. 927	○	○	○	5,50	2,90	10,00	14,14	20,00	6,20	24,49	31,62	44,72	950	1720
	616. 967	-	-	○	6,00	3,20	12,50	17,68	25,00	7,75	30,62	39,53	55,90	950	1720
	617. 047	-	-	○	8,00	4,40	20,00	28,28	40,00	12,41	48,99	63,25	89,44	950	1720

A = Equivalent bore diameter · E = narrowest free cross section
Subject to technical modifications.

The folded page at the end of the catalogue will give you a survey on the various assembly possibilities. For complete assembly accessories, please refer to „Accessories“.

Example	Type	+	Material no.	=	Ordering no.
for ordering:	616. 727	+	16	=	616. 727. 16