



Flat fan nozzles for retaining nut Series 656



Spray angle	Ordering no.				A ∅ [mm]	E ∅ [mm]	V̇ [l/min]						Spray width B at p = 2 bar		
	Type	Material-no.					p [bar]						 H = 250 mm H = 500 mm		
		16 1.4305/303 SS	17 1.4571/316 SS	30 Brass			0,5	1,0	2,0	[US gal/ min] at 40 psi	3,0	5,0			10,0
120°	656. 727	○	○	○	3,00	1,60	3,15	4,45	6,30	1,95	7,72	9,96	14,09	1240	2150
	656. 767	○	○	○	3,50	1,70	4,00	5,66	8,00	2,48	9,80	12,65	17,89	1240	2150
	656. 807	○	○	○	4,00	2,00	5,00	7,07	10,00	3,10	12,25	15,81	22,36	1240	2150
	656. 887	○	○	○	5,00	2,60	8,00	11,31	16,00	4,96	19,60	25,30	35,78	1240	2150
	656. 927	○	○	○	5,50	2,90	10,00	14,14	20,00	6,20	24,49	31,62	44,72	1240	2150

A = Equivalent bore diameter · E = narrowest free cross section
Subject to technical modifications.

Example	Type	+	Material no.	=	Ordering no.
for ordering:	656. 727	+	16	=	656. 727. 16

The folded page at the end of the catalogue will give you a survey on the various assembly possibilities.
For complete assembly accessories, please refer to „Accessories“.

