



Flat fan nozzles with dove-tail guide Series 664 / 665



Spray angle	Ordering no.			A ∅ [mm]	E ∅ [mm]	V̇ [l/min]							Spray width B at p = 2 bar		
	Type	Material-no.				p [bar]									
		16 1.4305/303 SS	17 1.4571/316 SS			30 Brass	0,5	1,0	2,0	[US gal./ min] at 40 psi	3,0	5,0			10,0
90°	664. 726	○	○	○	3,00	1,70	3,15	4,45	6,30	1,95	7,72	9,96	14,09	420	800
	664. 766	○	○	○	3,50	1,90	4,00	5,66	8,00	2,48	9,80	12,65	17,89	420	800
	664. 806	○	○	○	4,00	2,40	5,00	7,07	10,00	3,10	12,25	15,81	22,36	420	800
	664. 846	○	○	○	4,50	2,40	6,25	8,84	12,50	3,88	15,31	19,76	27,95	420	800
	664. 886	○	○	○	5,00	3,10	8,00	11,31	16,00	4,96	19,60	25,30	35,78	420	800
	664. 926	○	○	○	5,50	3,60	10,00	14,14	20,00	6,20	24,49	31,62	44,72	420	800
	664. 966	○	○	○	6,00	3,90	12,50	17,68	25,00	7,75	30,62	39,53	55,90	420	800
	665. 046	-	-	○	8,00	4,90	20,00	28,28	40,00	12,41	48,99	63,25	89,44	420	800
665. 126	-	-	○	10,00	6,40	31,50	44,55	63,00	19,54	77,16	99,61	140,87	420	800	
120°	664. 727	○	○	○	3,00	1,60	3,15	4,45	6,30	1,95	7,72	9,96	14,09	1240	2150
	664. 767	○	○	○	3,50	1,70	4,00	5,66	8,00	2,48	9,80	12,65	17,89	1240	2150
	664. 807	○	○	○	4,00	2,00	5,00	7,07	10,00	3,10	12,25	15,81	22,36	1240	2150
	664. 887	○	○	○	5,00	2,60	8,00	11,31	16,00	4,96	19,60	25,30	35,78	1240	2150
	664. 927	○	○	○	5,50	2,90	10,00	14,14	20,00	6,20	24,49	31,62	44,72	1240	2150
	664. 967	-	-	○	6,00	3,20	12,50	17,68	25,00	7,75	30,62	39,53	55,90	1240	2150
	665. 047	-	-	○	8,00	4,40	20,00	28,28	40,00	12,41	48,99	63,25	89,44	1240	2150

A = Equivalent bore diameter · E = narrowest free cross section
Subject to technical modifications.

Example	Type	+	Material no.	=	Ordering no.
for ordering:	664. 726	+	16	=	664. 726. 16



Accessories see next page.