









Tank cleaning nozzles

Self-rotating tank cleaning nozzles	Series		\dot{V} [l/min] at $p = 2$ bar	Connection	Application / Design	Page
	500. 234 566	180° 300° 360°	8 – 21	M6 3/8 BSPP	Cleaning of small tanks, up to 1,5 m in diameter. Self-rotating. Stainless steel versions.	7.5
	500. 186 500. 191	180° 300° 360°	13 – 20	1/2 BSPP	Cleaning of small tanks, up to 1,5 m in diameter. Self-rotating. Plastic versions.	7.6
	569	270° 360°	43 – 145	3/4 BSPP	Cleaning of tanks up to 3 m in diameter. Self-rotating. Double bearings.	7.7
	573/583	270° 360°	58 – 225	3/4 BSPP 1 BSPP Sanitary pin connection	Cleaning of tanks up to 3 m in diameter. Teflon Version. Self-rotating. Special version for CIP applications.	7.8
	ACCUClean 515/519 Stainless steel version	360°	97 – 419	3/4 BSPP 1 BSPP 1 1/2 BSPP	Cleaning of tanks up to 6 m in diameter. Self-rotating. Controlled rotation for maximum spray impact.	7.9



Tank cleaning nozzles

Static spray balls	Series		\dot{V} [l/min] at $p = 2$ bar	Connection	Application / Design	Page
	540	240°	18 - 28	1/2 BSPP	Cleaning of tanks up to 3 m in diameter. Static spray ball with sharp solid jets.	7.10
	591	180° 360°	49 - 460	Pin connection	Cleaning of tanks up to 5 m in diameter. Static spray ball for higher flow rates.	7.10