







# Accessories

## Ball joints

Allround swivelling action of 30°.  
 No sealings, no wear.  
 Long service life even after many adjustments.  
 P<sub>max</sub>: 25 bar.



For series	Ordering no.				Dimensions [mm]											Weight (Brass)
	Type	Material no.			Code	D <sub>1</sub>	D <sub>2</sub>	G <sub>1</sub>	G <sub>2</sub>	L <sub>G1</sub>	L <sub>G2</sub>	L	Hex 1	Hex 2	Hex 3	
		16	16	30												
422/460/544/612 632/686/688	092.020	-	1.4305/1.4571	1.4305/303 SS	AD	-	-	1/4 BSPP	1/4 BSPP	12,0	11,5	60,3	27	27	17	60 g
	092.021	-	1.4305/1.4571	1.4305/303 SS	AF	-	-	3/8 BSPP	1/4 BSPP	12,0	11,5	58,3	27	27	17	80 g
	092.030	-	1.4305/1.4571	1.4305/303 SS	AF	-	-	3/8 BSPP	3/8 BSPP	12,0	12,0	56,7	27	30	19	80 g
422/460/544/612 632/686/688	092.020	1.4305/1.4571	-	-	SD	20,0	15,0	-	1/4 BSPP	-	11,5	64,3	-	27	17	60 g
	092.030	1.4305/1.4571	-	-	SF	22,0	15,0	-	3/8 BSPP	-	12,0	58,7	-	30	19	80 g
216/302/468/652/679/684	092.022	-	1.4305/1.4571	1.4305/303 SS	AD	-	-	1/4 BSPP	3/8 BSPP	12,0	10,0	63,8	27	27	17	80 g
	092.022	-	1.4305/1.4571	1.4305/303 SS	AF	-	-	3/8 BSPP	3/8 BSPP	12,0	10,0	61,8	27	27	17	85 g
216/302/468/652/679/684	092.022	1.4305/1.4571	-	-	SE	20,0	15,0	-	3/8 BSPP	-	10,0	67,8	-	27	17	80 g

Example    Type    +    Material no.    +    Code    =    Ordering no.  
 for ordering: 092.020    +    16    +    AD    =    092.020.16.AD

